

Model Selection

Smart AC Charger BCP-A1N-L BCP-A2N-L BCP-B1N-L BCP-B2N-L



Category	Smart AC Charger
Maximum Power	7.4kW
Input Voltage /Output voltage	AC230 1-Phase
Input Frequency	50/60Hz
Meter	Metering Chip
Display	LED Lights
RFID	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>
APP	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>
Contact Adhesion Protection	<input checked="" type="checkbox"/>
Protection Degree	IP65
Environment Temperature	-25°C--+55°C
Maximum Altitude	<2000m

: Standard : Optional : Without

Smart AC Charger BCP-A1N-L-E BCP-A2N-L-E BCP-B1N-L-E BCP-B2N-L-E



Category	Smart AC Charger
Maximum Power	7.4kW
Input Voltage /Output voltage	AC230 1-Phase
Input Frequency	50/60Hz
Meter	Metering Chip
Display	LED Lights
RFID	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>
PEN	<input checked="" type="checkbox"/>
APP	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>
Over Voltage &Under Voltage Protection	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>
Contact Adhesion Protection	<input checked="" type="checkbox"/>
Protection Degree	IP65
Environment Temperature	-25°C--+55°C
Maximum Altitude	<2000m

: Standard : Optional : Without

Model Selection

Smart AC Charger BCP-AT1N-L BCP-AT2N-L BCP-BT1N-L BCP-BT2N-L



Category	Smart Version
Maximum Power	22kW
Input Voltage /Output voltage	AC400 3-Phase
Input Frequency	50/60Hz
Meter	Metering Chip
Display	LED Lights
RFID	<input checked="" type="checkbox"/>
DLB	<input type="checkbox"/>
Wi-Fi	<input checked="" type="checkbox"/>
APP	<input checked="" type="checkbox"/>
Bluetooth	<input checked="" type="checkbox"/>
Over Voltage & Under Voltage Protection	<input checked="" type="checkbox"/>
Emergency Stop	<input checked="" type="checkbox"/>
Over Current Protection	<input checked="" type="checkbox"/>
CP Signal Short Circuit Protection	<input checked="" type="checkbox"/>
Over Temperature Protection	<input checked="" type="checkbox"/>
Lightning Protection	<input checked="" type="checkbox"/>
Contact Adhesion Protection	<input checked="" type="checkbox"/>
Protection Degree	IP65 IP55
Environment Temperature	-25°C~+55°C
Maximum Altitude	<2000m

: Standard : Optional : Without

